

BLAST ATTENUATION DEVICE AND METHOD

BACKGROUND OF THE INVENTION

CROSS-REFERENCE TO RELATED APPLICATION

This application is a divisional of U.S. Application No. 10/313,834, filed December 6, 2002, which is hereby incorporated herein in its entirety by reference.

5

1) Field of the Invention

The present invention relates to the attenuation of blasts and, in particular, to apparatuses and methods for attenuating blasts with a shield formed of attenuation, or absorptive, material.

10

2) Description of Related Art

An explosion is typically characterized by a blast or sharp increase in pressure that propagates in a wavelike manner outward from a point or area of origination. Whether intentionally or unintentionally initiated, such blasts can result in severe damage to buildings, vehicles, and personnel. For example, a blast from a bomb that is detonated in a car parked near a building can cause structural damage to the building, damage components therein, and/or injure people within the building. Similarly, ballistic and aerial explosive devices can cause costly damage to buildings and other types of structures. An explosion originating in a cargo container can rupture the container and propagate therefrom. Explosive blasts can also travel through media other than air, for example, an underwater blast that propagates to a boat, submarine, or other vessel and inflicts damage.

15

20

The use of barriers for attenuating the blasts associated with explosions is well known. For example, buildings at risk of blast damage during battle conditions are sometimes protected by walls formed of concrete, sand bags, and the like. Such dense barriers provide a protective effect to an area by deflecting and/or attenuating the blast and thereby preventing the blast from reaching the protected area or at least reducing the momentum or overpressure of the blast that does propagate to the area. In some cases, however, the blast may refract over or around the barrier and propagate into the protected area. Additionally, the construction of barrier devices can be prohibitively

25

expensive, and such barriers can be impractical for protecting high structures, structures in densely populated regions, mobile structures, or underwater structures. Further, barriers can detract from the aesthetic appeal of a structure or area.

Thus, there exists a need for a blast attenuation device that provides an effective and space efficient shield for a protected area, including an area that includes a tall structure, a structure in a densely populated region, a mobile structure, or an underwater structure. The shield should be cost effective for construction, operation, and maintenance. Further, the shield should be adaptable to minimize the aesthetic impact of the shield or to render the shield aesthetically appealing.

BRIEF SUMMARY OF THE INVENTION

The present invention provides a system and method for producing a shield for protecting an area. The shield provides an attenuation of a pressure blast, and can be used with tall, mobile, and underwater structures, including structures in densely populated areas.

According to one embodiment, the present invention provides a shielding system for attenuating a pressure blast to shield a protected area. The system includes a source for providing an attenuation material, *i.e.*, an absorbing material, and a delivery system with a plurality of nozzles fluidly connected to the source by one or more passages. A valve device is configured to control the delivery of the attenuation material through the nozzles. The valve device can be actuated by a detector in response to a perceived blast threat, for example, an approach of a blast originator toward the protected area. In one embodiment, pipes are disposed at a peripheral area of a building, and the nozzles can be configured to direct the shield to extend substantially vertically and proximate to walls of the building.

The source can provide solid attenuation particulates, water or other liquids that the nozzles deliver as droplets, or a gas delivered as bubbles in a liquid medium. The attenuation material can be delivered as particulates having an average size of between about 0.01 mm and 1.0 mm, and the shield can have a three dimensional, or volumetric, packing factor of between about 0.001 and 0.01. According to one aspect, the packing factor is non-uniform across its thickness, for example, to generally increase in a direction from the origination toward the protected area.

According to another embodiment, the present invention provides a pressure attenuation shield for attenuating a pressure blast and shielding a structure. The shield

is formed of one or more sprays of attenuation material that are disposed proximate a periphery of the structure and between an origination of the pressure blast and the structure so that the shield attenuates the pressure blast by at least about 14.7 psi within a thickness of less than about 1 meter of the spray. According to one aspect, the shield includes first and second generally parallel walls disposed between an origination of the pressure blast and a protected area. A flexible host material such as a gelatinous fluid is disposed in the space between the walls, and an attenuation material is disposed as particulates suspended in the host material. The attenuation material is configured to attenuate the pressure blast and thereby reduce the pressure blast to below a damage threshold of a protected article in the protected area. The shield can be configured to form a cargo container.

The present invention also provides a method of attenuating a pressure blast to shield a protected area. The method includes detecting a threat of a pressure blast and, in response to the threat, spraying particulates to form the shield between an origination of the pressure blast and the protected area so that the shield attenuates the pressure blast from the origination.

Further, the present invention provides a method of constructing the system for attenuating a pressure blast and mitigating blast damage to a structure. The method includes determining a maximum initial pressure against which the structure is to be protected, determining an acceptable pressure to which the structure may be subjected, and selecting an attenuation material comprised of particles having a desired radius, mass density, and three-dimensional packing factor. A minimum thickness is determined, for example, according to a mathematical expression, for a particle mist of the attenuation material required to reduce the initial pressure to the acceptable pressure. A delivery system is mounted to the exterior surface of the structure such that the system is capable of providing the particle mist at least as thick as the determined minimum thickness.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

Figure 1 is perspective view of a blast attenuation system adapted to mitigate damage to a building according to one embodiment of the present invention;

Figure 2 is a chart illustrating the thicknesses of blast attenuation shields of different particulate materials that are required for attenuating blast pressures to a final pressure of 0.25 psi;

Figure 3 is a plan view of a blast shield with a non-uniform packing factor that partially reflects, partially attenuates, and partially transmits a blast shield according to one embodiment of the present invention;

Figure 4 is a perspective view of a blast attenuation system adapted to mitigate damage to an underwater structure according to another embodiment of the present invention; and

Figure 5 is a perspective view of a shield that is configured to form a cargo container according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present inventions now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the inventions are shown. Indeed, these inventions may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout.

Referring now to the figures, and in particular Figure 1, there is shown a blast attenuation system **10** according to one embodiment of the present invention, which is configured to provide an attenuation shield **70** around a protected area **80**. The blast attenuation system **10** can similarly be used to protect other areas of any size and shape. Each protected area **80** can also include one or more structures such as buildings **82** or vehicles. The blast attenuation system **10** includes a delivery system **12** that includes a network of passages, such as pipes **14**, disposed at an outer periphery **84** of the protected area **80**. The pipes **14** can be formed of metal or plastic, and can be conventional pipes that are used in water distribution systems. The pipes **14** can be made an integral part of the building **82**, for example, by locating the pipes **14** partially within the exterior walls of the building **82**. Alternatively, the pipes **14** can be mounted on the exterior of the building **82** as shown in Figure 1, for example, by adding the attenuation system **10** to the exterior of an existing building to thereby improve the protection of the building from blast damage. In any case, the attenuation system **10** can be designed to be visually unobtrusive or appealing, for example, by

decorating the pipes **14** in a color or style that complements the exterior walls of the building **82**.

The pipes **14** are fluidly connected to a source that provides an attenuation material for delivery through the pipes **14**. The attenuation material can be a solid,
5 liquid, or gas, as further described below. The source can be a water pipe that delivers water from a ground water supply **16** such as a public water supply system. Preferably, the source includes a reservoir that holds a volume of the attenuation material sufficient to provide the protective shield for at least a predetermined duration. For example, a water reservoir **18** can be located at the top of the building
10 **82** and fluidly connected to the ground water supply **16** so that the attenuation system **10** remains operational even if a connection **20** to the ground water supply **16** is interrupted. The reservoir can also provide the attenuation material to other systems of the building **82**, for example, a sprinkler system or other fire extinguishing system.

The attenuation system **10** can be operated continuously, but preferably a
15 valve device **22** is configured to control the flow of the attenuation material from the reservoir **18** to the delivery system **12** so that the attenuation system **10** can be turned on and off by adjusting the valve device **22** between open and closed positions. The valve device **22** can be manually operable so that an operator can initiate the system **10**, for example, to deploy the attenuation shield in response to a perceived blast
20 threat. The valve device **22** can also be automatically operable by one or more detectors **24** configured to detect the perceived blast threat. For example, each detector **24** can be an optical or electromagnetic device adapted for detecting motion or heat and thereby detecting an unauthorized entry or approach to the protected area **80**, such as an entry through a barricade, fence, or restricted area. The detector **24** can
25 also be configured to receive a signal transmitted from a communication device or input by an operator. In one advantageous embodiment of the invention, the valve device **22** and detector **24** are configured to react quickly to the perceived blast threat so that the valve device **22** can be repositioned in response to a possible blast originator, such as a vehicle, entering the detection zone outside the protected area **80**,
30 and the shield **70** can be deployed before the possible originator reaches an outer periphery of the shield **70**. The valve device **22** can be a fast-acting solenoid or pyrotechnic valve, for example, with a response time of 0.10 milliseconds or less.

The pipes **14** or other passages of the delivery system **12** are configured to deliver the attenuation matter to a plurality of nozzles **26**. Preferably, the nozzles **26**

are configured to deliver the attenuation material proximate to the periphery **84** of the protected area **80** and at least partially and, more commonly, completely surrounding the protected area **80**. For example, the pipes **14** can extend horizontally around the protected area **80** so that the protected area **80** is entirely enclosed horizontally, and
5 the nozzles **26** can be configured to spray the attenuation material to form the shield **70** vertically. The pipes **14** can also be disposed at multiple elevations, thereby providing a uniform shield, which can be deployed more quickly and more uniformly than a shield sprayed from a single pipe. For example, as illustrated in Figure 1, the protected area **80** includes the building **82**, and the pipes **14** are disposed at the top of
10 the building **82** and at incrementally lower levels. Upon initiation of the system **10** depicted in Figure 1, each of the nozzles **26** can begin spraying the attenuation material to form the shield **70** vertically. The shield **70** horizontally surrounds the building **82** such that a pressure blast originating outside the protected area **80** must propagate through the shield **70** to horizontally enter the protected area **80**. The
15 delivery system **12** can also extend over or under parts of the enclosed area **80**, such as over a roof of the building **82**, so that the shield **70** extends horizontally to protect the protected area **80** from vertical propagation of the pressure blast.

The shield **70** can be formed of any type of material or combination of materials. In addition to liquids such as water, the attenuation material can comprise
20 any solid materials, for example, sand, grains, or polystyrene foam in particulate form, such as Styrofoam[®] pellets. By the term “solid” it is not meant that the attenuation particles must be solid throughout. For example, the attenuation material can comprise shelled objects such as hollow balls similar to the type commonly used for table tennis, which are formed of celluloid or other polymer materials. Solid
25 attenuation particulates can be delivered through the delivery system **12** described above, for example, by blowing air through the delivery system **12** to propel the solid particulates to the nozzles **26**, which can be adapted for delivering the solid particulates. The particulates can be collected in bins or drains located at the lower periphery of the protected area **80** below the nozzles **26**, and the particulates can be
30 reclaimed for re-use in the attenuation system **10** or for other uses. Further, the delivery system **12** can be configured to deliver the attenuation material in any direction. For example, the delivery system **12** can be disposed at the peripheral base of the protected area and configured to deliver the attenuation material upwards to form a vertically extending shield. The delivery system **12** can comprise pipes, as

described above, or the attenuation material can be delivered from a tray or channel, which can also be used to reclaim the attenuation material.

The effective attenuation of the shield is influenced by the pressure blast, a thickness **D** of the shield **70**, a radius **r** and density ρ_p of the individual particles of the attenuation material, a three-dimensional packing factor **F** of the attenuation material, and a density ρ_a of the ambient medium. The packing factor **F** is the ratio of the number of particles in a specific volume of the shield **70** relative to the maximum number of particles that can be disposed in the same volume. In one advantageous embodiment of the invention, the packing factor **F** is between about 0.001 and 0.01.

For cases where the density ρ_p of the particles of the attenuation material is much greater than the density ρ_a of the ambient medium, the required thickness **D** of the shield **70** for attenuating an initial pressure **P_i** due to the pressure blast to a final pressure **P_f** can be approximated by assuming that the attenuation material behaves according to a Brownian motion model. For example, the required thickness **D** can be determined according to the following equation:

$$D = 1.24 \frac{r}{F^{\frac{11}{12}}} \left(\frac{\rho_p}{\rho_a} \right)^{\frac{1}{4}} \left[\ln \left(\frac{P_i}{P_f} \right) \right]^{\frac{1}{2}}$$

where the initial and final pressures **P_i**, **P_f** are measured as overpressures or gauge pressures, *i.e.*, pressures measured above the ambient pressure. Thus, if water is used as the attenuation material in an atmosphere of air at 100 kPa, the density ρ_p of the particles is about 1 grams/cubic centimeter and, the density ρ_a of the air is about 1.3 kilogram/cubic meter, and the thickness **D** of the shield **70** is given by:

$$D = 6.53 \frac{r}{F^{\frac{11}{12}}} \left[\ln \left(\frac{P_i}{P_f} \right) \right]^{\frac{1}{2}}.$$

The thickness **D** of the shield **70** can be designed and adjusted according to the pressure blast threat and the necessary protection. For example, a bomb detonated outside the building **82** could cause a pressure blast to propagate to the building **82** and cause an initial overpressure pressure **P_i** of about 100 kPa (14.7 psi) to occur temporarily outside the shield **70**. Conventional windows, such as windows **83** on the building **82** of Figure 1, typically break when subjected to an overpressure of about 0.5 psi, *i.e.*, when the pressure outside the building **82** is 0.5 psi higher than the pressure within the building **82**. Figure 2 illustrates the attenuation effect of shields

formed of sand, water, and polystyrene foam pellets with particles of radius r of 0.1 mm and a packing factor F of 0.001. As shown, the required thickness D for attenuating the blast to a final overpressure of 0.25 psi, *i.e.*, so that the final pressure P_f is only 0.25 psi higher than the ambient pressure, varies according to the
5 attenuation material and the initial overpressure P_i . By reducing the final overpressure to only 0.25 psi, a safety factor of two is provided for preventing breakage of the windows 83 that are able to withstand an overpressure of 0.5 psi.

A variety of materials can be used for attenuation, and the thickness D can be adjusted according to the desired protection and the attenuation material. For
10 example, an attenuation shield of water droplets with a radius r of 0.1 mm, a packing factor F of 0.001, and a thickness D of about 75 cm would reduce the initial pressure P_i of 100 kPa (14.7 psi) to a final pressure P_f of 0.25 psi, thus significantly reducing the probability that the windows 83 at the exterior of the building 82 will break. If the shield 70 is formed of droplets that are larger, for example, about 1 mm, the packing
15 factor F can be increased to provide a similar attenuation effect. Similarly, if the shield is formed of a particles that are more or less dense than water, the thickness D or the packing factor F can be increased to provide a similar attenuation effect. Preferably, the attenuation material, radius r , and packing factor F , are selected so that the shield 70 attenuates an expected blast with an initial pressure P_i greater than
20 100 kPa by at least about 0.1 psi per cm of thickness D . For example, the shield 70 can be configured to attenuate such a blast by least about 14.7 psi within a thickness of less than about 1 meter of the shield 70.

Further, the shield 70 can partially reflect the pressure blast away from the protected area 80 and thereby provide an additional protective effect to mitigate
25 damage due to the blast. For example, upon impinging on the shield 70, a pressure blast is partially reflected and partially transmitted due to the variation in impedance characteristics between the shield 70 and the ambient medium that results from the mismatched densities ρ_p, ρ_a . Transmission into the shield 70 is enhanced if the densities ρ_p, ρ_a and, hence, the impedances of the shield 70 and the ambient medium
30 are closely matched, and reflectance is increased if the impedances are mismatched. In one embodiment, the nozzles 26 are configured to deliver the attenuation matter so that the shield 70 is non-uniform, or stratified, throughout its thickness so that the shield 70 defines a packing factor F that is higher in some portions of the shield 70 and lower in other portions. The shield 70 can be configured so that the non-

uniformities affect the reflectance and absorption characteristics of the shield 70. For example, as shown in Figure 3, the packing factor **F** can be made to increase in a direction extending from an origination 86 of a pressure blast toward the protected area 80 so that the pressure blast first impinges on the portion of the shield 70 where the packing factor **F** is lowest and then propagates through shield portions with increasingly higher packing factors **F**. Thus, the impedance of the shield 70 at an outer periphery of the shield 70 is closely matched to the ambient medium, and the reflection of the blast is minimized so that the pressure blast is transmitted into the shield 70 and attenuated therein. Further, the nozzles 26 are configured to deliver the attenuation material such that the packing factor **F** is highest at an inner periphery of the shield 70 so that the impedance of the shield 70 is mismatched with the ambient medium. Thus, after the pressure blast propagates to the inner periphery of the shield 70, the impedance mismatch causes the blast to be partially reflected away from the protected area 80 and transmitted again through the shield 70 for further attenuation therein. Alternatively, the nozzles 26 can be configured to deliver the attenuation material such that the shield 70 has a high packing factor **F** at its outer periphery so that initial reflectance of the pressure blast is increased. In some cases, absorption of the pressure blast may be preferable to reflectance. For example, if the building 82 is located among other structures, reflectance of the pressure blast therefrom may increase the damage to the other nearby structures. Further, subsequent reflections of the blast may impinge on other portions of the building 82 that are not protected by the shield 70, such as the roof of the building 82.

According to another advantageous embodiment of the present invention, the attenuation material can comprise a gas such as air disposed as bubbles in a liquid medium. For example, Figure 4 illustrates a delivery system 12 that comprises a network of pipes 14 configured at the periphery 84 of the protected area 80 that includes an underwater structure 88 such as a submarine. The nozzles 26 are configured to deliver the air to form bubbles in the ambient medium, which is water in this embodiment. The air bubbles, which rise in the water, provide a shield 70a for protecting the protected area 80 from pressure blasts that propagate through the water, for example, originating from an underwater explosive such as a depth charge. The shield 70a can provide an attenuating effect similar to the effect described above. Additionally, the impedance mismatch between the shield 70a and the water can result in significant reflectance of the pressure blast away from the protected area

thereby decreasing the final pressure P_f of the blast that propagates to the protected area **80** and mitigating the damage of the blast.

Although the shields **70**, **70a** are described above as a spray of the attenuation material, the particulates of the attenuation material can alternatively be configured as a static shield. For example, solid particulates can be embedded in a solid or liquid medium such as a flexible host material, such as sponge, feathers, foam, or gel, which is positioned between the protected area and the possible location of a blast origination. In one embodiment, illustrated in Figure 5, a shield **70b** is configured to form a double-hulled cargo container **100**. The container **100** defines a space between an inner wall **102** and an outer wall **104**. Particulates **72** of the attenuation material are disposed between the inner and outer walls **102**, **104**, in the flexible host material that fills space. For example, particulates formed of sand, foam, or other materials can be disposed in any a gelatinous fluid or any other flexible host material. The shield **70b** can be used to mitigate damage outside the container **100**, that results from a blast originating within the container **100** or to mitigate damage within the container **100** from a blast outside the container **100**. For example, if a bomb that is transported within the container **100** explodes, the shield **70b** would mitigate damage to the vehicle transporting the container **100** as well as other cargo being transported by the vehicle. Preferably, the shield **70b** provides sufficient attenuation to reduce an expected pressure blast to below a damage threshold of articles in the protected area. The protected articles can include cargo in the container **100**, other cargo near the container **100**, a vehicle used to transport the container **100**, and the like. The appropriate thickness **D** of the shield **70b** can be determined according to the foregoing discussion.

Many modifications and other embodiments of the inventions set forth herein will come to mind to one skilled in the art to which these inventions pertain having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the inventions are not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.